

# NORD Lift 60 V3 - OTTO 1500

Optimize your internal logistics by automating the transportation of pallets or other types of payloads with the Nord Modules Lift top module. The NORD Lift 60 autonomously picks up and delivers payloads in the P&D Stand.

Ensures stable handling and transport of payload. It enables the OTTO 1500 AMR to lift payloads autonomously from the P&D Stand and lowers the lifting platform for stable transportation of payloads up to 1500 kg.

The NORD Lift 60 is equipped with strategically placed holes atop its structure, tailor-made to accommodate various tooling options. This feature adds a valuable dimension to its functionality, making it a versatile solution for your internal logistics needs.



## NORD compatibility



NORD P&D Stand Cantilever 1200 V1 - OTTO 1500

## OTTO compatibility



OTTO 1500

Designated use	For autonomous pickup and unload of payloads
Product name	Nord Lift 60 V3 - OTTO 1500
Robot compatibility	OTTO 1500
NORD compatibility	NORD P&D Cantilever Stand 1200 V1 - OTTO 1500
Weight	150 kg   330 lbs
Max payload capacity	1 500 kg   3 307 lbs
Expected lifespan	Minimum 600 000 lifts at max payload

*Disclaimer*

*Specifications may vary based on local conditions and application*



Can handle uneven weight distribution



High level of feedback



600.000+ lifts




High industrial level of quality



Max payload of 1500 kg

# Specifications



## Additional Features

1. Tooling mount locations	Threaded holes in the platform and frame
2. Blue light signal interface	Connection available for a blue light
3. Stack lights	Front & rear - operating-level & service status
4. Payload detection sensor	2 sensors to detect presence of payload

## Performance

Function	Manual override buttons
Lifting speed	Up: 4 s - Down: 4s
Data collection	Error codes + data transfer to AMR
Motion type	Servo technology

## Dimensions

Length	1 458 mm   57.4 in
Length (of the platform)	1 238 mm   48.7 in
Width	1 085 mm   42.7 in
Width (of the platform)	794 mm   31.3 in
Height	99 mm   3.9 in
Total height (when mounted on AMR)	450 mm   17.72 in
Lifting height	60 mm   2.36 in